

Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 1 (10)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ALD C-11 INTRELEVEN BHA

IFF Code: 00093760MSDS Number: R00000224847Product Use Description: Fragrance Ingredient

Company : IFF Benicarló, S.L.

Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone : +34964470212 Telefax : +34964473411 Emergency telephone number : +34 964 470 212

SECTION 2 HAZARDS IDENTIFICATION

GHS-Classification

Flammable liquids, Category 4 Skin irritation, Category 2 Eye irritation, Category 2A Skin sensitisation, Category 1 Skin sensitisation, Sub-category 1B

GHS-Labelling

Symbol(s)

Signal word : Warning

Hazard statements : H227: Combustible liquid.

H315: Causes skin irritation.

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 2 (10)

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

Precautionary statements : P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/ eye protection/ face protection.

Carcinogenicity:

IARC	TERT-BUTYL-4-	25013-16-5, 121-00-6
	METHOXYPHENOL	

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP	TERT-BUTYL-4-	25013-16-5	
	METHOXYPHENOL		

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Component	CAS-No.
undec-9-enal, undec-10-enal, undec-8-enal	112-45-8, 143-14-6, 58296- 81-4
Phenol, (1,1-dimethylethyl)-4-methoxy-	25013-16-5, 121-00-6

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 3 (10)

SECTION 4. FIRST AID MEASURES

First aid procedures

Inhalation : Remove from exposure site to fresh air and keep at rest. Obtain

medical advice.

Skin contact : Remove contaminated clothes. Wash thoroughly with water (and

soap). Contact physician if symptoms persist.

Eye contact : Flush immediately with water for at least 15 minutes. Contact

physician if symptoms persist.

Ingestion : Rinse mouth with water and obtain medical advice.

SECTION 5. FIREFIGHTING MEASURES

Flammable properties

Flash point : 174.20 °F (79.00 °C)

Fire fighting

Suitable extinguishing media : Use water spray, dry chemical, carbon dioxide or appropriate foam.

Protective equipment and precautions for firefighters

Special protective equipment for

firefighters

Wear NIOSH approved self-contained breathing apparatus and full

protective clothing when fighting fires involving chemicals. Use

water spray to cool containers exposed to fire.

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 4 (10)

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Avoid inhalation and contact with skin and eyes. A self-contained

breathing apparatus is recommended in case of a major spill.

Environmental precautions : Keep away from drains, surface- and groundwater and soil.

Methods for containment / Methods for cleaning up

: Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Gross spillages should be contained by use of sand or inert powder and

disposed of according to the local regulations.

SECTION 7. HANDLING AND STORAGE

Handling : Avoid excessive inhalation of concentrated vapors. Follow good

manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned

before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be

restricted to properly trained employees.

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire and explosion

Keep away from ignition sources and naked flame.

Requirements for storage areas and

containers

Store in a cool, dry, ventilated area away from heat sources. Keep

containers upright and tightly closed when not in use.

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 5 (10)

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures

Engineering measures : Where feasible, isolate mixing rooms and other areas where this

material is used or openly handled. Maintain these areas under

negative air pressure relative to the rest of the plant.

Where feasible, use closed systems to transfer and process this

material

Personal protective equipment

Eye protection : Use tight-fitting goggles, face shield or safety glasses with side

shields if eye contact might occur.

Hand protection : Avoid skin contact. Use chemically resistant gloves.

Respiratory protection : Use local exhaust ventilation around open tanks and other open

sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to

eliminate or reduce possible worker exposures.

No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation,

etc. are sufficient.

If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or

canisters and particulate filters should be used:

a) while engineering controls and appropriate safe work practices

and/or procedures are being implemented; or

b)during short term maintenance procedures when engineering

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 6 (10)

controls are not in normal operation or are not sufficient; or c)if normal operational workplace vapor concentration in the air is increased due to heat;

d)during emergencies; or

e)if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational exposure limit.

Hygiene measures

To the extent deemed appropriate, implement pre-placement and regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to this material.

To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air to determine potential exposures and to ensure the continuing effectiveness of engineering controls and operational practices to minimize exposure.

Protective measures

: In December 2003, the National Institute for Occupational Safety and Health ("NIOSH") published an Alert on preventing lung disease in workers who use or make flavorings [NIOSH Publication Number 2004-110].

In August 2004, the United States Flavor and Extract Manufacturers Association (FEMA) issued a report entitled "Respiratory Safety in the Flavor Manufacturing Workplace".

Both of these reports provide recommendations for reducing employee exposure and for medical surveillance in the workplace. The recommendations in these reports are generally applicable to the use of any chemical in the workplace and you are strongly urged to review both of these reports.

The report published by FEMA also contains a list of "high priority" chemicals. If any of these chemicals are present in this product at a concentration >= 1.0% due to an intentional addition by IFF, the chemical(s) will be identified in this safety data sheet.

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 7 (10)

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state : liquid Colour : colorless

Odour : conforms to standard

Safety data

Flash point : 174.20 °F (79.00 °C)

Vapour pressure : .04 hPa (0.04 hPa)

Note: Calculated

Relative density (20 °C) : 0.8420 - 0.8470

Partition coefficient: n-octanol/water : log Pow: 3.970

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid : Remarks: Direct sources of heat.

Chemical stability : Remarks: Presents no significant reactivity hazard, by itself or in

contact with water. Avoid contact with strong acids, alkali or

oxidizing agents.

Hazardous decomposition products : Note: Carbon monoxide and unidentified organic compounds may

be formed during combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 8 (10)

Acute oral toxicity : Acute toxicity estimate

Dose: > 5,000 mg/kg

Method: Calculation method

Acute oral toxicity (Component) : Component: 112-45-8

LD50 Rat

Dose: > 5,000 mg/kg Remarks: RIFM

Acute dermal toxicity : Component: 112-45-8

(Component) LD50 Rabbit

Dose: > 5,000 mg/kg

Skin irritation (Component) : Component: 112-45-8

human

Result: No skin irritation Method: closed patch test Exposure time: 48 h

Rabbit

Result: Skin irritation Exposure time: 24 h

Sensitisation (Component) : Component: 112-45-8

maximisation study human

Result: Did not cause sensitisation on laboratory animals.

Test substance: 5% in petrolatum

Repeated dose : Component: 112-45-8

toxicity(Component)

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 9 (10)

Contaminated packaging : Place material into sealed containers and dispose of in accordance

with local, state and federal regulations.

SECTION 14. TRANSPORT INFORMATION

DOT Proper shipping name : Combustible liquid, n.o.s.

(UNDECENAL)

UN number : 1993 Class : CBL Packing group : III Emergency Response : 128

Guidebook Number

DOT NON-BULK Not dangerous goods

IATA Not dangerous goods

IMDG Not dangerous goods

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard

Reportable Quantity :

HMIS Classification : Health hazard: 1

Flammability: 2

Physical and chemical hazards: 0

SECTION 16. OTHER INFORMATION

Further information

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L.IFF Benicarló, S.L.Avda. Felipe Klein 2Avda. Felipe Klein 212580 BENICARLÓ12580 BENICARLÓ



Product ALD C-11 INTRELEVEN BHA

Print Date 08/13/2015 Page 10 (10)

The information in this MSDS was obtained from current and reliable sources. However the data is provided without any warrant, expressed or implied, regarding its correctness or accuracy. Since the use, handling, storage and disposal of this product are beyond IFF control, it is the responsibility of the user both to determine safe conditions for the use of this product and to assume liability of loss, damage, or expense arising out of the product's improper use. No warranty expressed or implied regarding the product described herein shall be created by or inferred from any statement or omission in this MSDS. Various Federal, State or Provincial agencies may have specific regulations concerning the transportation, handling, storage, use, or disposal of this product which may not be reflected in this MSDS. The user should review these regulations to ensure full compliance.

Version : 3

Revision Date : 08/03/2015

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ