

Product MUGUET ALDEHYDE 50 DEP

Print Date 06/10/2020 Page 1 (9)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : MUGUET ALDEHYDE 50 DEP

IFF Code: 00138650Cust. Material: 00138650SDS Number: R00000002905Product Use Description: Fragrance Ingredient

Company : IFF Benicarló, S.L.

Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone : +34964470212 Telefax : +34964473411 Emergency telephone number : +34 964 470 212

SECTION 2 HAZARDS IDENTIFICATION

GHS-Classification

Skin irritation, Category 2 Eye irritation, Category 2A Skin sensitisation, Category 1

GHS-Labelling

Symbol(s) :

Signal word : Warning

Hazard statements : H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

Precautionary statements : P280: Wear protective gloves/ eye protection/ face protection.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for

Version : 5

Revision Date : 06/10/2020

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product MUGUET ALDEHYDE 50 DEP

Print Date 06/10/2020 Page 2 (9)

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SECTION 4. FIRST AID MEASURES

First aid procedures

Inhalation : Remove from exposure site to fresh air and keep at rest. If victim is

unconscious, remove foreign bodies from the mouth. If victim has stopped breathing, give artificial respiration. Obtain medical advice.

Skin contact : Remove contaminated clothes. Wash thoroughly with water (and

soap). Contact physician if symptoms persist.

Eye contact : Flush immediately with water for at least 15 minutes. Contact

physician if symptoms persist.

Ingestion : Rinse mouth with water and obtain medical advice.

SECTION 5. FIREFIGHTING MEASURES

Flammable properties

Flash point : $> 201 \, ^{\circ}\text{F} (> 94 \, ^{\circ}\text{C})$

Version : 5

Revision Date : 06/10/2020

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product MUGUET ALDEHYDE 50 DEP

Print Date 06/10/2020 Page 3 (9)

Fire fighting

Suitable extinguishing media : Use water spray, dry chemical, carbon dioxide or appropriate foam.

Protective equipment and precautions for firefighters

Special protective equipment for firefighters

Wear NIOSH approved self-contained breathing apparatus and full protective clothing when fighting fires involving chemicals. Use water spray to cool containers exposed to fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Avoid inhalation and contact with skin and eyes. A self-contained

breathing apparatus is recommended in case of a major spill.

Environmental precautions : Keep away from drains, surface- and groundwater and soil.

Methods for containment / Methods for cleaning up

: Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

SECTION 7. HANDLING AND STORAGE

Handling : Avoid excessive inhalation of concentrated vapors. Follow good

manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned

before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be

restricted to properly trained employees.

Version :

Revision Date : 06/10/2020

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product MUGUET ALDEHYDE 50 DEP

Print Date 06/10/2020 Page 4 (9)

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire

and explosion

Keep away from ignition sources and naked flame.

Requirements for storage areas and

containers

Store in a cool, dry, ventilated area away from heat sources. Keep

containers upright and tightly closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	Listed by	Value type	Exposure limit(s)
1,2- Benzenedicarboxyli c acid, 1,2-diethyl ester	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time-weighted average	5 mg/m3
1,2- Benzenedicarboxyli c acid, 1,2-diethyl ester	USA. NIOSH Recommended Exposure Limits	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek	5 mg/m3
1,2- Benzenedicarboxyli c acid, 1,2-diethyl ester	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	8-hour time weighted average	5 mg/m3
1,2- Benzenedicarboxyli c acid, 1,2-diethyl ester	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	Permissible exposure limit	5 mg/m3

Engineering measures

Engineering measures : Where feasible, isolate mixing rooms and other areas where this

material is used or openly handled. Maintain these areas under

negative air pressure relative to the rest of the plant.

Where feasible, use closed systems to transfer and process this

material

Personal protective equipment

Version : 5

Telephone: +34964470212

Revision Date : 06/10/2020

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ

Telefax: +34964473411



MUGUET ALDEHYDE 50 DEP Product

Print Date 06/10/2020 Page 5 (9)

Eye protection

: Use tight-fitting goggles, face shield or safety glasses with side

shields if eye contact might occur.

Hand protection

: Avoid skin contact. Use chemically resistant gloves.

Respiratory protection

: Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures.

No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation, etc. are sufficient.

If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or canisters and particulate filters should be used:

a) while engineering controls and appropriate safe work practices and/or procedures are being implemented; or

b)during short term maintenance procedures when engineering controls are not in normal operation or are not sufficient; or c)if normal operational workplace vapor concentration in the air is increased due to heat;

d)during emergencies; or

e)if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational

exposure limit.

Hygiene measures

To the extent deemed appropriate, implement pre-placement and regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to this material.

To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air to determine potential exposures and to ensure the continuing effectiveness of engineering controls and

operational practices to minimize exposure.

Protective measures

: In December 2003, the National Institute for Occupational Safety and Health ("NIOSH") published an Alert on preventing lung

Version

Revision Date : 06/10/2020

IFF Benicarló, S.L. Avda. Felipe Klein 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 12580 BENICARLÓ

Telephone: +34964470212 Telefax: +34964473411



Product MUGUET ALDEHYDE 50 DEP

Print Date 06/10/2020 Page 6 (9)

disease in workers who use or make flavorings [NIOSH Publication Number 2004-110].

In August 2004, the United States Flavor and Extract Manufacturers Association (FEMA) issued a report entitled "Respiratory Safety in the Flavor Manufacturing Workplace".

Both of these reports provide recommendations for reducing employee exposure and for medical surveillance in the workplace. The recommendations in these reports are generally applicable to the use of any chemical in the workplace and you are strongly urged to review both of these reports.

The report published by FEMA also contains a list of "high priority" chemicals. If any of these chemicals are present in this product at a concentration >= 1.0% due to an intentional addition by IFF, the chemical(s) will be identified in this safety data sheet.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state : liquid

Appearance : CLEAR LIQUID
Colour : pale yellow to yellow

Odour : conforms to standard

Safety data

Flash point : $> 201 \, ^{\circ}\text{F} (> 94 \, ^{\circ}\text{C})$

Vapour pressure : .01 hPa (0.01 hPa)

Note: Calculated

Relative density (20 °C) : 0.9650 - 0.9850

Partition coefficient: n-octanol/water : log Pow: 3.260

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid : Remarks: Direct sources of heat.

Version : 5

Revision Date : 06/10/2020

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product MUGUET ALDEHYDE 50 DEP

Print Date 06/10/2020 Page 7 (9)

Chemical stability : Remarks: Presents no significant reactivity hazard, by itself or in

contact with water. Avoid contact with strong acids, alkali or

oxidizing agents.

Hazardous decomposition products : Note: Carbon monoxide and unidentified organic compounds may

be formed during combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Toxicological information

Further information : There is no data available for this product. The health hazards are

assessed based on the ingredients in this preparation and their

concentrations.

SECTION 12. ECOLOGICAL INFORMATION

Ecological information

Additional ecological information : Avoid contamination of soil, ground and surface water.

SECTION 13. DISPOSAL CONSIDERATIONS

Contaminated packaging : Place material into sealed containers and dispose of in accordance

with local, state and federal regulations.

SECTION 14. TRANSPORT INFORMATION

DOT Not dangerous goods

IATA UN number : 3082

Description of the goods : ENVIRONMENTALLY HAZARDOUS

Version : 5

Revision Date : 06/10/2020

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product MUGUET ALDEHYDE 50 DEP

Print Date 06/10/2020 Page 8 (9)

SUBSTANCE, LIQUID, N.O.S.

(Acetaldehyde, [(3,7-dimethyl-6-octenyl)oxy]-)

Class : 9
Packing group : III
ICAO-Labels : 9

IMDG UN number : 3082

Description of the goods : ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S.

(Acetaldehyde, [(3,7-dimethyl-6-octenyl)oxy]-)

Class : 9
Packing group : III
IMDG-Labels : 9
EmSNumber 1 : F-A
EmSNumber 2 : S-F
Marine pollutant : yes

(Acetaldehyde, [(3,7-dimethyl-6-octenyl)oxy]-)

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

Reportable Quantity :

HMIS Classification : Health hazard: 2

Chronic Health Hazard: /

Flammability: 1

Physical and chemical hazards: 0

SECTION 16. OTHER INFORMATION

Further information

Version : 5

Revision Date : 06/10/2020

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ



Product MUGUET ALDEHYDE 50 DEP

Print Date 06/10/2020 Page 9 (9)

The information in this MSDS was obtained from current and reliable sources. However the data is provided without any warrant, expressed or implied, regarding its correctness or accuracy. Since the use, handling, storage and disposal of this product are beyond IFF control, it is the responsibility of the user both to determine safe conditions for the use of this product and to assume liability of loss, damage, or expense arising out of the product's improper use. No warranty expressed or implied regarding the product described herein shall be created by or inferred from any statement or omission in this MSDS. Various Federal, State or Provincial agencies may have specific regulations concerning the transportation, handling, storage, use, or disposal of this product which may not be reflected in this MSDS. The user should review these regulations to ensure full compliance.

Version : 5

Revision Date : 06/10/2020

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ

IFF Benicarló, S.L. Avda. Felipe Klein 2 12580 BENICARLÓ