

Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 1 (11)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name

CITRAL DIMETHYL ACETAL

IFF Code

00034233

Cust. Material SDS Number

00034233 R00000216591

Product Use Description

Fragrance Ingredient

Company

IFF Inc.

600 Highway 36 Hazlet NJ 07730

Telephone

(732) 264-4500

Telefax

(732) 335-2551

Emergency telephone number

+1 800 424 9300

SECTION 2 HAZARDS IDENTIFICATION

GHS-Classification

Flammable liquids, Category 4 Acute toxicity, Category 4, Oral Skin irritation, Category 2 Eye irritation, Category 2A Skin sensitisation, Category 1

GHS-Labelling

Symbol(s)

:

Signal word

Warning

Hazard statements

H227: Combustible liquid. H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

Precautionary statements

: P210: Keep away from heat/sparks/open flames/hot surfaces. No

Version

: 5

Revision Date

: 08/07/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 2 (11)

smoking.

P280: Wear protective gloves/ eye protection/ face protection. P301 + P312 + P330: IF SWALLOWED: Call a POISON

CENTER/doctor if you feel unwell. Rinse mouth.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Component	CAS-No.	
2,6-Octadiene, 1,1-dimethoxy-3,7-dimethyl-	7549-37-3	

SECTION 4. FIRST AID MEASURES

Telephone: +17322644500

First aid procedures

Inhalation : Remove from exposure site to fresh air and keep at rest. If victim is

unconscious, remove foreign bodies from the mouth. If victim has stopped breathing, give artificial respiration. Obtain medical advice.

Skin contact : Remove contaminated clothes. Wash thoroughly with water (and

soap). Contact physician if symptoms persist.

soap). Contact physician it symptoms persist.

Eye contact : Flush immediately with water for at least 15 minutes. Contact

physician if symptoms persist.

Version

Revision Date

: 08/07/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 3 (11)

Ingestion

: Rinse mouth with water and obtain medical advice.

SECTION 5. FIREFIGHTING MEASURES

Flammable properties

Flash point

180.00 °F (82.22 °C)

Fire fighting

Suitable extinguishing media

: Use water spray, dry chemical, carbon dioxide or appropriate foam.

Protective equipment and precautions for firefighters

Special protective equipment for

Methods for containment /

firefighters

Wear NIOSH approved self-contained breathing apparatus and full protective clothing when fighting fires involving chemicals. Use

water spray to cool containers exposed to fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Avoid inhalation and contact with skin and eyes. A self-contained Personal precautions

breathing apparatus is recommended in case of a major spill.

Keep away from drains, surface- and groundwater and soil. Environmental precautions

Clean up spillage promptly. Remove ignition sources. Provide

adequate ventilation. Avoid excessive inhalation of vapours. Gross Methods for cleaning up

spillages should be contained by use of sand or inert powder and

disposed of according to the local regulations.

SECTION 7. HANDLING AND STORAGE

: Avoid excessive inhalation of concentrated vapors. Follow good Handling

Version

5

Revision Date

: 08/07/2019

600 Highway 36 Hazlet NJ 07730 600 Highway 36

Telephone: +17322644500

Telefax: +17323352551



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 4 (11)

manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be restricted to properly trained employees.

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire and explosion

Keep away from ignition sources and naked flame.

Requirements for storage areas and containers

Store in a cool, dry, ventilated area away from heat sources. Keep

containers upright and tightly closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	Listed by	Value type	Exposure limit(s)
2,6-Octadienal, 3,7-dimethyl-	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time-weighted average	5 ppm
Methanol	USA. ACGIH Threshold Limit Values (TLV)	8-hour, time-weighted average	200 ppm
Methanol	USA. ACGIH Threshold Limit Values (TLV)	Short-term exposure limit	250 ppm
Methanol	USA. NIOSH Recommended Exposure Limits	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek	200 ppm 260 mg/m3
Methanol	USA. NIOSH Recommended Exposure Limits	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday	250 ppm 325 mg/m3

Version

Revision Date

Telephone: +17322644500

: 5

: 08/07/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 5 (11)

M-411	LICA Occupational European	8-hour time weighted average	200 ppm
Methanol	USA. Occupational Exposure	8-nour time weighted average	260 mg/m3
	Limits (OSHA) - Table Z-1 Limits	-	200 mg/m3
	for Air Contaminants		
Methanol	USA. OSHA - TABLE Z-1 Limits	Short-term exposure limit	250 ppm
	for Air Contaminants - 1910.1000		325 mg/m3
Methanol	USA. OSHA - TABLE Z-1 Limits	8-hour time weighted average	200 ppm
	for Air Contaminants - 1910.1000		260 mg/m3
Methanol	California permissible exposure	Ceiling	1,000 ppm
	limits for chemical contaminants		
	(Title 8, Article 107)		
Methanol	California permissible exposure	Permissible exposure limit	200 ppm
	limits for chemical contaminants	-	260 mg/m3
	(Title 8, Article 107)		
Methanol	California permissible exposure	Short term exposure limit	250 ppm
	limits for chemical contaminants	•	325 mg/m3
	(Title 8, Article 107)		

Engineering measures

Engineering measures

: Where feasible, isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under

negative air pressure relative to the rest of the plant.

Where feasible, use closed systems to transfer and process this

material

Personal protective equipment

Eye protection

: Use tight-fitting goggles, face shield or safety glasses with side

shields if eye contact might occur.

Hand protection

: Avoid skin contact. Use chemically resistant gloves.

Respiratory protection

: Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to

eliminate or reduce possible worker exposures.

No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation,

etc. are sufficient.

Version

Revision Date

5

: 08/07/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 6 (11)

If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or canisters and particulate filters should be used:

a) while engineering controls and appropriate safe work practices and/or procedures are being implemented; or

b)during short term maintenance procedures when engineering controls are not in normal operation or are not sufficient; or c)if normal operational workplace vapor concentration in the air is increased due to heat:

d)during emergencies; or

e)if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational exposure limit.

Hygiene measures

: To the extent deemed appropriate, implement pre-placement and regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to this material.

To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air to determine potential exposures and to ensure the continuing effectiveness of engineering controls and operational practices to minimize exposure.

Protective measures

: In December 2003, the National Institute for Occupational Safety and Health ("NIOSH") published an Alert on preventing lung disease in workers who use or make flavorings [NIOSH Publication Number 2004-110].

In August 2004, the United States Flavor and Extract Manufacturers Association (FEMA) issued a report entitled "Respiratory Safety in the Flavor Manufacturing Workplace".

Both of these reports provide recommendations for reducing employee exposure and for medical surveillance in the workplace. The recommendations in these reports are generally applicable to the use of any chemical in the workplace and you are strongly urged to review both of these reports.

The report published by FEMA also contains a list of "high priority" chemicals. If any of these chemicals are present in this product at a concentration >= 1.0% due to an intentional addition by IFF, the chemical(s) will be identified in this safety data sheet.

Version Revision Date 5

: 08/07/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 7 (11)

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state

: liquid

Appearance Colour

: CLEAR LIQUID

colorless to pale yellow

Odour

: conforms to standard

Safety data

Flash point

180.00 °F (82.22 °C)

Vapour pressure

: .03 hPa (0.03 hPa) Note: Calculated

Relative density (20 °C)

: 0.8860 - 0.8940

Partition coefficient: n-octanol/water : log Pow: 3.574

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid

: Remarks: Direct sources of heat.

Chemical stability

Remarks: Presents no significant reactivity hazard, by itself or in contact with water. Avoid contact with strong acids, alkali or

oxidizing agents.

Hazardous decomposition products

: Note: Carbon monoxide and unidentified organic compounds may

be formed during combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

: Acute toxicity estimate

Version

5

Revision Date

08/07/2019

600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500

600 Highway 36 Hazlet NJ 07730

Telefax: +17323352551



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 8 (11)

Dose: 1,325 mg/kg

Method: Calculation method

Acute oral toxicity (Component)

Component: 5392-40-5

LD50 Rat

Dose: 4,950 mg/kg

Component: 67-56-1

LD50 Rat

Dose: 5,628 mg/kg Remarks: Sax

Acute dermal toxicity

: Acute toxicity estimate

Dose: 2,493 mg/kg

Method: Calculation method

Acute dermal toxicity

(Component)

: Component: 5392-40-5

LD50 Rabbit Dose: 2,250 mg/kg

Component: 67-56-1

LD50

Dose: 15,800 mg/kg

Acute inhalation toxicity

Acute toxicity estimate Exposure time: 4 h

Dose: 166.68 mg/l

Method: Calculation method

Acute inhalation toxicity

(Component)

: Component: 67-56-1

Dose: 64000 ppm

Skin irritation (Component)

Component: 5392-40-5

Rabbit

Result: irritating Remarks: rabbit skin

Component: 67-56-1

Rabbit

Result: Skin irritation Exposure time: 24 h

Eye irritation(Component)

Component: 67-56-1

Version

Revision Date

: 5

: 08/07/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 9 (11)

Rabbit

Result: Eye irritation Exposure time: 24 h Test substance: (undiluted)

Sensitisation (Component)

Component: 5392-40-5

Maximisation Test Guinea pig Result: Causes sensitisation.

Repeated dose

toxicity(Component)

Component: 5392-40-5

SECTION 12. ECOLOGICAL INFORMATION

Component:

5392-40-5

Citral

Toxicity to fish:

static test LC50

Species: Leuciscus idus (Golden orfe)

Dose: 4.6 - 10 mg/l Exposure time: 96 h Method: DIN 38412

Supplier

Toxicity to daphnia and other aquatic invertebrates:

static test EC50

Species: Daphnia magna (Water flea)

Dose: 7 mg/l Exposure time: 48 h

Method: Directive 67/548/EEC, Annex V, C.2.

Supplier

Toxicity to algae: static testEC50

Species: Desmodesmus subspicatus (green algae)

Dose: 103.8 mg/l Exposure time: 72 h Method: DIN 38412

The product has low solubility in the test medium. An

aqueous dispersion was tested.

Toxicity to bacteria:

EC50

Species: Pseudomonas putida

Version

Revision Date

: 5

: 08/07/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730

Telefax: +17323352551

Telephone: +17322644500



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 10 (11)

Dose: 2,100 mg/l Exposure time: 0.5 h

The product has low solubility in the test medium. An

aqueous dispersion was tested.

Additional ecological information:

The product has low solubility in the test medium. An

aqueous dispersion was tested.

SECTION 13. DISPOSAL CONSIDERATIONS

Contaminated packaging

: Place material into sealed containers and dispose of in accordance

with local, state and federal regulations.

SECTION 14. TRANSPORT INFORMATION

DOT

Proper shipping name

: Combustible liquid, n.o.s.

()

Labels UN number : NONE : 1993

Class
Packing group

: CBL : III

Emergency Response Guidebook Number : 128

DOT NON-BULK

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

SECTION 15, REGULATORY INFORMATION

Telephone: +17322644500

SARA 311/312 Hazards

: Fire Hazard

Acute Health Hazard

Reportable Quantity

•

HMIS Classification

: Health hazard: 0

Version

: 5

Revision Date

: 08/07/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730



Product

CITRAL DIMETHYL ACETAL

Print Date

12/12/2019

Page 11 (11)

Flammability: 0 Physical and chemical hazards: 0

SECTION 16. OTHER INFORMATION

Further information

The information in this MSDS was obtained from current and reliable sources. However the data is provided without any warrant, expressed or implied, regarding its correctness or accuracy. Since the use, handling, storage and disposal of this product are beyond IFF control, it is the responsibility of the user both to determine safe conditions for the use of this product and to assume liability of loss, damage, or expense arising out of the product's improper use. No warranty expressed or implied regarding the product described herein shall be created by or inferred from any statement or omission in this MSDS. Various Federal, State or Provincial agencies may have specific regulations concerning the transportation, handling, storage, use, or disposal of this product which may not be reflected in this MSDS. The user should review these regulations to ensure full compliance.

Version Revision Date : 5

: 08/07/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NI 07730

Telephone: +17322644500

Telefax: +17323352551