



**SECTION A-A**

**NOTES:**

1. MODIFIED BUTTRESS THREAD (6 PITCH).
2. .060 MINIMUM SEALING LAND REQUIRED.
3. ORIFICE SIZE OPTIONS AVAILABLE: 1/8" AND 1/4"
4. KNURLS: .012 DEEP
5. CONTACT BERRY PLASTICS FOR LATEST REVISION.
6. OPENING FORCE RANGE IS 1.5 - 5 LBS.



TITLE:  
**28-410 ACC-1 SE**

MATERIAL:  
PP

SCALE:  
2.00; NOTED

**NOTICE**  
THIS UNPUBLISHED WORK IS THE PROPERTY OF BERRY PLASTICS CORPORATION AND IS PROTECTED BY TRADE SECRET, COPYRIGHT AND OTHER INTELLECTUAL PROPERTY LAWS AND MAY ALSO BE SUBJECT TO A SPECIFIC OR GENERAL CONFIDENTIALITY AGREEMENT. IT IS NOT TO BE VIEWED BY UNAUTHORIZED PERSONS OR DUPLICATED IN ANY MEDIUM FOR PURPOSES OTHER THAN THOSE FOR WHICH IT IS SPECIFICALLY FURNISHED. IN THE EVENT OF PUBLICATION, THE FOLLOWING NOTICE SHALL APPLY

DSGN'D BY:  
KSK  
DATE:  
04-June-09

DRAWN BY:  
KSK  
DATE:  
04-June-09

CHK'D BY:  
  
DATE:

APP'D BY:  
  
DATE:

DRAWING NO. REV.  
**K9836**  
SHEET 1 OF 1