SDS Type: GHS / OSHA

DOC ID: 41666.993928.1028963

Product: Pikaki

 Product#:
 78788 Page 1 of 7

 SKU#:
 pik 2014-01-29

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade Name: Pikaki
Product/Sales No: 78788

1.2 Relevant indentified product use

Intended use: Compound used in customer substance/mixture/product

1.3 Details of the manufacturer/supplier of the saftey data sheet

Wellington Fragrance 33306 Glendale St. Livonia, MI 48150 USA

734-261-5531 Fax 734-261-5571

wellingtonfragrance.com

1.4 Emergency telephone number

(800) 255-3924 Domestic USA, Canada, Puerto Rico, and US Virgin Islands

+1 813 248-0585 International (CHEMTEL #MIS 0000533)

2. Hazards Identification

2.1 Classification of the substance or mixture

This mixture has not been tested as a whole. The effects, listed below, are based on evaluation of individual components in accordance with the provisions of the regulation(s) noted below.

Classification according to GHS Regulation (EC) No 1272/2008

Aquatic Acute Toxicity, Category 2 :

Acute Toxicity Oral, Category 5 H303: May be harmful if swallowed

Acute Toxicity Dermal, Category 5 H313: May be harmful in contact with skin

Skin Corrosion/Irritation, Category 3 H316: Causes mild skin irritation

Sensitization, Skin, Category 1B H317: May cause an allergic skin reaction

Eye Damage/Eye Irritation, Category 2A H319: Causes serious eye irritation Acute Toxicity Inhalation, Category 5 H333: May be harmful if inhaled

Aquatic Chronic Toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects

Classification OSHA (Provisions 1910.1200 of title 29)

Flammability Class IIIB Combustible Liquid
Acute Dermal/Eye 12 : Causes skin irritation.

15: May cause eye irritation.

Acute Inhalation 23 : May cause respiratory tract irritation.

25: Inhalation at high levels may cause: anesthesia, tremors, labored breathing,

hypothermia, lethargy, ataxia.

Acute Oral 3: May be harmful if swallowed.

Reproductive/Developmental 39 : Causes reproductive/developmental toxicity in animals.

Sensitization/Allergic Response 31: May cause allergic skin reaction.

Target Organ Effects 26: Prolonged or repeated ingestion may cause damage to: kidneys, liver,

stomach, brain, tongue, mucous membranes, musculo-skeletal system.

28 : Prolonged or repeated Dermal Exposure may cause damage to: kidneys, skin

Carcinogenicity This mixture contains ingredients identified as carcinogens, at 0.1% or greater,

by the following: None [X] ACGIH [] IARC [] NTP [] OSHA []

SDS Type: GHS / OSHA

Safety Data Sheet

DOC ID: 41666.993928.1028963

Product: Pikaki

Product#: **78788** Page 2 of 7 SKU#: **pik** 2014-01-29

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal Word: Warning Hazard statments

| H303 | May be harmful if swallowed |
|------|---|
| H313 | May be harmful in contact with skin |
| H316 | Causes mild skin irritation |
| H317 | May cause an allergic skin reaction |
| H319 | Causes serious eye irritation |
| H333 | May be harmful if inhaled |
| H411 | Toxic to aquatic life with long lasting effects |

Precautionary Statements

Prevention:

P264 Wash hands thoroughly after handling

P272 Contaminated work clothing should not be allowed out of the workplace

P273 Avoid release to the environment

Response:

P302 + P352 IF ON SKIN: Wash with soap and water

P304 + P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes Remove contact lenses if

present and easy to do. continue rinsing

P312 Call a POISON CENTER or doctor/physician if you feel unwell P333 + P313 If skin irritation or a rash occurs: Get medical advice/attention

P337 + P313 If eye irritation persists: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P391 Collect Spillage

2.3 Other Hazards

no data available

3. Composition/Information on Ingredients

3.1 Mixtures

This product is a complex mixture of ingredients, which contains among others the following substance(s), presenting a health or environmental hazard within the meaning of the UN Globally Harmonized System of Classification and Labeling of Chemicals (GHS):

| CAS# | EC# | Conc. | | |
|------------|-----|-------|--------------------|---------------------|
| Ingredient | EG# | Range | GHS Classification | OSHA Classification |

SDS Type: GHS / OSHA

DOC ID: 41666.993928.1028963

Product: Pikaki Product#: 78788 SKU#: pik

Page 3 of 7 2014-01-29

| CAS# Ingredient | EC# | Conc. Range | GHS Classification | OSHA Classification |
|--------------------|---------------------|-------------------|------------------------|---------------------|
| 8050-15-5 | 232-476-2 | 20 - 30 % | H412 | 31 |
| Methyl es | ster of rosin (par | tially hydrogena | ted) | |
| 140-11-4 | 205-399-7 | 20 - 30 % | H227; H303; H316 | 15, 25, 26, 31, 39 |
| Benzyl ad | cetate | | | |
| 120-51-4 | 204-402-9 | 10 - 20 % | H302; H313; H411 | 28, 3 |
| Benzyl B | enzoate | | | |
| 101-86-0 | 202-983-3 | 5 - 10 % | H303; H316; H317; H411 | 11, 15 |
| Hexyl cin | namal | | | |
| 78-70-6 | 201-134-4 | 2 - 5 % | H227; H303; H315; H319 | 12, 26 |
| Linalool | | | | |
| 118-58-1 | 204-262-9 | 2 - 5 % | H303; H317; H320; H412 | 31 |
| Benzyl Sa | alicylate | | | |
| 65405-77-8 | 265-745-8 | 2 - 5 % | H410 | 11, 15 |
| cis-3-Hex | enyl salicylate | | | |
| 93-16-3 | 202-224-6 | 2 - 5 % | H303; H316 | 12, 31 |
| Methyl is | oeugenol (Isoeu | igenyl methyl etl | ner) | |
| 24851-98-7 | 246-495-9 | 2 - 5 % | H316 | |
| Methyldih | nydrojasmonate | | | |
| 134-20-3 | 205-132-4 | 2 - 5 % | H303; H316; H319 | 11, 15 |
| Methyl ar | nthranilate | | | |
| 100-51-6 | 202-859-9 | 2 - 5 % | H302; H313; H319; H332 | 11, 15, 23, 25, 31 |
| Benzyl Al | lcohol | | | |
| See Section 1 | 16 for full text of | GHS classificat | ion codes | |

Total Hydrocarbon Content (% w/w) = 0.00

First Aid Measures

Description of first aid measures

Inhalation: Remove from exposure site to fresh air and keep at rest.

Obtain medical advice.

Eye Exposure: Flush immediately with water for at least 15 minutes.

Contact physician if symptoms persist.

Remove contaminated clothes. Wash thoroughly with water (and soap). **Skin Exposure:**

Contact physician if symptoms persist.

Ingestion: Rinse mouth with water and obtain medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: no data available

Risks: Refer to Section 2.2 "Hazard Statements"

4.3 Indication of any immediate medical attention and special treatment needed

Refer to Section 2.2 "Response" **Treatment:**

SDS Type: GHS / OSHA

DOC ID: 41666.993928.1028963

Product: Pikaki

Product#: **78788** Page 4 of 7 SKU#: **pik** 2014-01-29

5. Fire-Fighting measures

5.1 Extinguishing media

Suitable: Carbon dioxide (CO2), Dry chemical, Foam

UnsuitableDo not use a direct water jet on burning material

5.2 Special hazards arising from the substance or mixture

During fire fighting: Water may be ineffective

5.3 Advice for firefighters

Further information: Standard procedure for chemical fires

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.

6.2 Environmental precautions

Keep away from drains, soil, and surface and groundwater.

6.3 Methods and materials for containment and cleaning up

Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapors. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

6.4 Reference to other sections

Not Applicable

7. Handling and Storage

7.1 Precautions for safe handling

Apply according to good manufacturing and industrial hygiene practices with proper ventilation. Do not drink, eat or smoke while handling. Respect good personal hygiene.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry and ventilated area away from heat sources and protected from light in tightly closed original container. Avoid plastic and uncoated metal container. Keep air contact to a minimum.

7.3 Specific end uses

No information available

8. Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits:

Component

ACGIH ACGIH OSHA OSHA
TWA ppm STEL ppm TWA ppm STEL ppm

140-11-4 Benzyl acetate 10

Engineering Controls: Use local exhaust as needed.

8.2 Exposure controls - Personal protective equipment

Eye protection: Tightly sealed goggles, face shield, or safety glasses with brow guards and side shields, etc.

as may be appropriate for the exposure

SDS Type: GHS / OSHA

DOC ID: 41666.993928.1028963

Product: Pikaki

Product#: **78788** Page 5 of 7 SKU#: **pik** 2014-01-29

Respiratory protection: Avoid excessive inhalation of concentrated vapors. Apply local ventilation where appropriate.

Skin protection: Avoid Skin contact. Use chemically resistant gloves as needed.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Conforms to Standard

Odor: Conforms to Standard

Tint to Pale Yellow

Viscosity: Liquid

Freezing Point:

Boiling Point:

Melting Point:

Not determined

Not determined

Not determined

Flashpoint:

>200 F (93.33 C)

Auto flammability:

Not determined

Explosive Properties:

None Expected

Oxidizing properties:

 Vapor Pressure (mmHg@20 C):
 0.0335

 %VOC:
 23.6

 Specific Gravity @ 25 C:
 1.0430

 Density @ 25 C:
 1.0400

 Refractive Index @ 25 C:
 1.5240

 Soluble in:
 Oil

10. Stability and Reactivity

10.1 Reactivity None10.2 Chemical stability Stable

10.3 Possibility of hazardous reactions None known10.4 Conditions to avoid None known

10.5 Incompatible materials Strong oxidizing agents, strong acids, and alkalis

10.6 Hazardous decomposition products None known

11. Toxicological Information

11.1 Toxicological Effects

Acute toxicity - Oral (LD50: 2,645.50) May be harmful if swallowed

Acute toxicity - Dermal (LD50: 4,464.29) May be harmful in contact with skin

Acute toxicity - Inhalation (LC50: 24.20) May be harmful if inhaled

Skin corrosion / irritation

Causes mild skin irritation

Serious eye damage / irritation

Causes serious eye irritation

SDS Type: GHS / OSHA

DOC ID: 41666.993928.1028963

Product: Pikaki

 Product#:
 78788 Page 6 of 7

 SKU#:
 pik 2014-01-29

Respiratory sensitization Not classified - the classification criteria are not met

Skin sensitization May cause an allergic skin reaction

Germ cell mutagenicity

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Not classified - the classification criteria are not met

Aspiration hazard Not classified - the classification criteria are not met

12. Ecological Information

12.1 Toxicity

Acute acquatic toxicity

Chronic acquatic toxicity

Toxic to aquatic life with long lasting effects

Toxicity Data on soilno data availableToxicity on other organismsno data available

12.2 Persistence and degradabilityno data available12.3 Bioaccumulative potentialno data available12.4 Mobility in soilno data available12.5 Other adverse effectsno data available

13. Disposal Conditions

13.1 Waste treatment methods

Do not allow product to reach sewage systems. Dispose of in accordance with all local and national regulations. Send to a licensed waste management company. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. Transport Information

| Regulator | | Class | Pack Group | Sub Risk | UN-nr. | | |
|---|------------|---------------|-----------------|----------|--------|--|--|
| U.S. DOT (Non-Bulk) | | Not Regulated | - Not Dangerous | s Goods | | | |
| Chemicals NOI | | | | | | | |
| ADR/RID (International Road/Rail) | | | | | | | |
| Environmentally Hazardous Liquid, n.o.s. IATA (Air Cargo) | Substance, | 9 | III | | UN3082 | | |
| Environmentally Hazardous Liquid, n.o.s. IMDG (Sea) | Substance, | 9 | III | | UN3082 | | |
| Environmentally Hazardous Liquid, n.o.s. | Substance, | 9 | III | | UN3082 | | |

SDS Type: GHS / OSHA

DOC ID: 41666.993928.1028963

Product: **Pikaki** Product#: **78788**

Product#: **78788** Page 7 of 7 SKU#: **pik** 2014-01-29

15. Regulatory Information

U.S. Federal Regulations:

TSCA (Toxic Substance Control Act): All components of the substance/mixture are listed or exempt

40 CFR(EPCRA, SARA, CERCLA and CAA)

U.S. State Regulations:

This product contains NO components of concern.

California Proposition 65 Warning No Warning required

Canadian Regulations:

DSL / NDSL 100.00% of the components are listed or exempt.

16. Other Information

GHS H-Statements referred to under section 3

H227 : Combustible liquid H302 : Harmful if swallowed

H303 : May be harmful if swallowed H313 : May be harmful in contact with skin

H315 : Causes skin irritation
H316 : Causes mild skin irritation
H317 : May cause an allergic skin reaction
H319 : Causes serious eye irritation

H320 : Causes eye irritation H332 : Harmful if inhaled

H410 : Very toxic to aquatic life with long lasting effects

H411 : Toxic to aquatic life with long lasting effects

H412: Harmful to aquatic life with long lasting effects

Total Fractional Values

(TFV) Risk (TFV) Risk

(10.68) Aquatic Acute Toxicity, Category 2
 (6.20) Sensitization, Skin, Category 1B
 (4.40) Skin Corrosion/Irritation, Category 3
 (1.41) Eye Damage/Eye Irritation, Category 2A

Department issuing data sheet:

(2.67) Aquatic Chronic Toxicity, Category 2

Department E-mail address:

Remarks

This safety data sheet is based on the properties of the material known to Wellington Fragrance at the time the data sheet was issued. The safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances, under which it is packaged, stored or applied in the workplace. For such a safety assessment Welling holds no responsibility. This document is not intended for quality assurance purposes.