

Product

PRENYL ACETATE

Print Date

06/24/2019

Page 1 (9)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name

PRENYL ACETATE

IFF Code

00166416

Cust. Material SDS Number

00166416 R00000226611

Product Use Description

Fragrance Ingredient

· .

Company

IFF Inc.

600 Highway 36 Hazlet NJ 07730

Telephone Telefax (732) 264-4500 (732) 335-2551

Emergency telephone number

+1 800 424 9300

SECTION 2 HAZARDS IDENTIFICATION

GHS-Classification

Flammable liquids, Category 3

GHS-Labelling

Symbol(s)

:

Signal word

Warning

Hazard statements

: H226: Flammable liquid and vapour.

Precautionary statements

: P210: Keep away from heat/sparks/open flames/hot surfaces. No

smoking.

Version

: 3

Revision Date

: 06/04/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500



Product

PRENYL ACETATE

Print Date

06/24/2019

Page 2 (9)

P240: Ground/bond container and receiving equipment. P403 + P235: Store in a well-ventilated place. Keep cool.

Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS-No.

: 1191-16-8

Hazardous components

Component	CAS-No.
2-Buten-1-ol, 3-methyl-, 1-acetate	1191-16-8

SECTION 4. FIRST AID MEASURES

First aid procedures

Inhalation : Remove from exposure site to fresh air and keep at rest. If victim is

unconscious, remove foreign bodies from the mouth. If victim has stopped breathing, give artificial respiration. Obtain medical advice.

Skin contact : Remove contaminated clothes. Wash thoroughly with water (and

soap). Contact physician if symptoms persist.

Eye contact : Flush immediately with water for at least 15 minutes. Contact

physician if symptoms persist.

Version : 3

Revision Date : 06/04/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500



Product

PRENYL ACETATE

Print Date

06/24/2019

Page 3 (9)

Ingestion

: Rinse mouth with water and obtain medical advice.

SECTION 5. FIREFIGHTING MEASURES

Flammable properties

Flash point

120.99 °F (49.44 °C)

Fire fighting

Suitable extinguishing media

: Use water spray, dry chemical, carbon dioxide or appropriate foam.

Protective equipment and precautions for firefighters

Special protective equipment for

firefighters

: Wear NIOSH approved self-contained breathing apparatus and full protective clothing when fighting fires involving chemicals. Use

water spray to cool containers exposed to fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions

: Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.

Environmental precautions

Keep away from drains, surface- and groundwater and soil.

Methods for containment / Methods for cleaning up

/

: Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Gross spillages should be contained by use of sand or inert powder and

disposed of according to the local regulations.

Version

Revision Date

: 06/04/2019

: 3

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500



Product

PRENYL ACETATE

Print Date

06/24/2019

Page 4 (9)

SECTION 7. HANDLING AND STORAGE

Handling

: Avoid excessive inhalation of concentrated vapors. Follow good manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be restricted to properly trained employees.

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire and explosion

: Keep away from ignition sources and naked flame.

Requirements for storage areas and containers

Store in a cool, dry, ventilated area away from heat sources. Keep containers upright and tightly closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures

Engineering measures

: Where feasible, isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant.

Where feasible, use closed systems to transfer and process this

material

Version

Revision Date

: 3

: 06/04/2019

600 Highway 36 Hazlet NJ 07730 600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500



Product

PRENYL ACETATE

Print Date

06/24/2019

Page 5 (9)

Personal protective equipment

Eye protection

: Use tight-fitting goggles, face shield or safety glasses with side

shields if eye contact might occur.

Hand protection

: Avoid skin contact. Use chemically resistant gloves.

Respiratory protection

: Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures.

No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation,

etc. are sufficient.

If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or canisters and particulate filters should be used:

a) while engineering controls and appropriate safe work practices

and/or procedures are being implemented; or

b)during short term maintenance procedures when engineering controls are not in normal operation or are not sufficient; or c)if normal operational workplace vapor concentration in the air is increased due to heat;

d)during emergencies; or

e)if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational

exposure limit.

Hygiene measures

To the extent deemed appropriate, implement pre-placement and regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to

this material.

Version Revision Date : 3

: 06/04/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500 Telefax: +17323352551



Product

PRENYL ACETATE

Print Date

06/24/2019

Page 6 (9)

To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air to determine potential exposures and to ensure the continuing effectiveness of engineering controls and operational practices to minimize exposure.

Protective measures

: In December 2003, the National Institute for Occupational Safety and Health ("NIOSH") published an Alert on preventing lung disease in workers who use or make flavorings [NIOSH Publication Number 2004-110].

In August 2004, the United States Flavor and Extract Manufacturers Association (FEMA) issued a report entitled "Respiratory Safety in

the Flavor Manufacturing Workplace".

Both of these reports provide recommendations for reducing employee exposure and for medical surveillance in the workplace. The recommendations in these reports are generally applicable to the use of any chemical in the workplace and you are strongly urged to review both of these reports.

The report published by FEMA also contains a list of "high priority" chemicals. If any of these chemicals are present in this product at a concentration >= 1.0% due to an intentional addition by IFF, the chemical(s) will be identified in this safety data sheet.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state

: liquid

Appearance Colour CLEAR LIQUID

: colorless

Odour

: conforms to standard

Safety data

Version

Revision Date

: 3

: 06/04/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500



Product

PRENYL ACETATE

Print Date

06/24/2019

Page 7 (9)

Flash point

: 120.99 °F (49.44 °C)

Vapour pressure

: 2.53 hPa (2.53 hPa) Note: Calculated

Relative density (20 °C)

: 0.9140 - 0.9240

Partition coefficient: n-octanol/water

: log Pow: 1.650

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid

: Remarks: Direct sources of heat.

Chemical stability

: Remarks: Presents no significant reactivity hazard, by itself or in

contact with water. Avoid contact with strong acids, alkali or

oxidizing agents.

Hazardous decomposition products

: Note: Carbon monoxide and unidentified organic compounds may

be formed during combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

: Acute toxicity estimate

Dose: 3,000 mg/kg

Method: Calculation method

SECTION 12. ECOLOGICAL INFORMATION

Version

Revision Date

: 06/04/2019

: 3

IFF Inc. 600 Highway 36 Hazlet NJ 07730

600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500



Product

PRENYL ACETATE

Print Date

06/24/2019

Page 8 (9)

SECTION 13. DISPOSAL CONSIDERATIONS

Contaminated packaging

: Place material into sealed containers and dispose of in accordance

with local, state and federal regulations.

SECTION 14. TRANSPORT INFORMATION

DOT

Proper shipping name

: Combustible liquid, n.o.s.

(PRENYL ACETATE)

Labels

UN number

NONE 1993

Class

CBL

Packing group

: 111

Emergency Response

Guidebook Number

: 128

DOT NON-BULK Not dangerous goods

IATA

UN number

: 3272

Description of the goods

: ESTERS, N.O.S.

(PRENYL ACETATE)

Class

3

Packing group ICAO-Labels

: 111 : 3

IMDG

UN number

: 3272

Description of the goods

: ESTERS, N.O.S.

(PRENYL ACETATE)

Class

3

Packing group

: 111

IMDG-Labels

: 3 : F-E

EmSNumber 1 EmSNumber 2

S-D

Marine pollutant

: no

Version

: 3

Revision Date

: 06/04/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730

Telephone: +17322644500



Product

PRENYL ACETATE

Print Date

06/24/2019

Page 9 (9)

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards

: Fire Hazard

Reportable Quantity

:

HMIS Classification

: Health hazard: 1

Flammability: 2

Physical and chemical hazards: 0

SECTION 16. OTHER INFORMATION

Further information

The information in this MSDS was obtained from current and reliable sources. However the data is provided without any warrant, expressed or implied, regarding its correctness or accuracy. Since the use, handling, storage and disposal of this product are beyond IFF control, it is the responsibility of the user both to determine safe conditions for the use of this product and to assume liability of loss, damage, or expense arising out of the product's improper use. No warranty expressed or implied regarding the product described herein shall be created by or inferred from any statement or omission in this MSDS. Various Federal, State or Provincial agencies may have specific regulations concerning the transportation, handling, storage, use, or disposal of this product which may not be reflected in this MSDS. The user should review these regulations to ensure full compliance.

Version

Revision Date

: 3

: 06/04/2019

IFF Inc. 600 Highway 36 Hazlet NJ 07730 IFF Inc. 600 Highway 36 Hazlet NJ 07730