

Product TIMBERSILK

Print Date 28.04.2015 Page 1 (7)

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

 Product name
 : TIMBERSILK

 IFF Code
 : 00201694

 Cust. Material
 : 00201694

 MSDS Number
 : 300000316429

Use of the Substance/Mixture : Ingredient used in Flavour and/or Fragrance preparations

Company : IFF Benicarló, S.L.

Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone : +34964470212 Emergency telephone number : +34 964 470 212

#### 2. HAZARDS IDENTIFICATION

#### **GHS-Classification**

Skin corrosion/irritation, Category 2 Skin sensitisation, Sub-category 1B Acute aquatic toxicity, Category 1 Chronic aquatic toxicity, Category 1

#### **GHS-Labelling**

Symbol(s)





Signal word : Warning

Hazard statements : H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements : P261: Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264: Wash skin thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the

workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P321: Specific treatment (see supplemental first aid instructions on

this label).

P333 + P313: If skin irritation or rash occurs: Get medical advice/

attention.

P362: Take off contaminated clothing and wash before reuse.

Version : 4

Revision Date : 04.03.2015



Product TIMBERSILK

Print Date 28.04.2015 Page 2 (7)

P391: Collect spillage.

P501: Dispose of contents/ container to an approved waste disposal

plant.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name of the substance : 1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-

one

Chemical characterization : alicyclic ketones
Molecular formula : C16H26O
Molecular weight : 234.2 g/mol

CAS-No. : 68155-66-8, 54464-57-2, 68155-67-9

EC-No. : 915-730-3

#### 4. FIRST AID MEASURES

Inhalation : Remove from exposure site to fresh air and keep at rest. Obtain

medical advice.

Skin contact : Remove contaminated clothes. Wash thoroughly with water (and

soap). Contact physician if symptoms persist.

Eye contact : Flush immediately with water for at least 15 minutes. Contact

physician if symptoms persist.

Ingestion : Rinse mouth with water and obtain medical advice.

#### 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbondioxide, dry chemical, foam.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Avoid inhalation and contact with skin and eyes. A self-contained

breathing apparatus is recommended in case of a major spill.

Environmental precautions : Keep away from drains, surface- and groundwater and soil.

Methods for cleaning up : Clean up spillage promptly. Remove ignition sources. Provide

adequate ventilation. Avoid excessive inhalation of vapours. Gross spillages should be contained by use of sand or inert powder and

disposed of according to the local regulations.

#### 7. HANDLING AND STORAGE

#### Handling

Advice on safe handling : Avoid excessive inhalation of concentrated vapors. Follow good

manufacturing practices for housekeeping and personal hygiene.

Version : 4

Revision Date : 04.03.2015



Product TIMBERSILK

Print Date 28.04.2015 Page 3 (7)

Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be restricted to properly trained employees.

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire and explosion

Advice on protection against fire and : Keep away from ignition sources and naked flame.

#### **Storage**

Requirements for storage areas and containers

Store in a cool, dry, ventilated area away from heat sources. Keep containers upright and tightly closed when not in use.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Verify if the substances declared in section 3 have relevant national exposure limits.

#### Personal protective equipment

Respiratory protection

: Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures.

No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation, etc. are sufficient.

If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or canisters and particulate filters should be used:

a) while engineering controls and appropriate safe work practices and/or procedures are being implemented; or

b)during short term maintenance procedures when engineering controls are not in normal operation or are not sufficient; or c)if normal operational workplace vapor concentration in the air is increased due to heat;

d)during emergencies; or

e)if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational

Version : 4

Revision Date : 04.03.2015



Product TIMBERSILK

Print Date 28.04.2015 Page 4 (7)

exposure limit.

Hygiene measures : To the extent deemed appropriate, implement pre-placement and

regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to

this material.

To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air to determine potential exposures and to ensure the continuing effectiveness of engineering controls and

operational practices to minimize exposure.

Protective measures : In December 2003, the National Institute for Occupational Safety

and Health ("NIOSH") published an Alert on preventing lung disease in workers who use or make flavorings [NIOSH Publication

Number 2004-110].

In August 2004, the United States Flavor and Extract Manufacturers Association (FEMA) issued a report entitled "Respiratory Safety in

the Flavor Manufacturing Workplace".

Both of these reports provide recommendations for reducing employee exposure and for medical surveillance in the workplace. The recommendations in these reports are generally applicable to the use of any chemical in the workplace and you are strongly urged to

review both of these reports.

The report published by FEMA also contains a list of "high priority" chemicals. If any of these chemicals are present in this product at a concentration >= 1.0% due to an intentional addition by IFF, the

chemical(s) will be identified in this safety data sheet.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state : liquid Colour : pale yellow

Odour : conforms to standard

Safety data

Flash point :  $> 100 \, ^{\circ}\text{C}$ 

Ignition temperature :  $> 100 \, ^{\circ}\text{C}$ 

Auto-ignition temperature : 260 °C

at 1,013 hPa

Method: Tested according to Annex V of Directive 67/548/EEC.

Boiling point : 290.00 °C

at 1,013 hPa Note: Calculated

Version : 4

Revision Date : 04.03.2015



Product **TIMBERSILK** 

Print Date 28.04.2015 Page 5 (7)

Vapour pressure < 0.01 hPa

Note: Calculated

Water solubility 0.00268 g/l

at 20 °C

Method: OECD Test Guideline 105

Partition coefficient: n-

octanol/water

: log Pow: 5.650

#### 10. STABILITY AND REACTIVITY

Conditions to avoid Remarks: Direct sources of heat.

Hazardous decomposition products : Note: Carbon monoxide and unidentified organic compounds may

be formed during combustion.

Hazardous reactions : Presents no significant reactivity hazard, by itself or in contact with

water. Avoid contact with strong acids, alkali or oxidizing agents.

#### 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity LD50 (Rat) = > 5,000 mg/kgLD50 (Rat) = > 5,000 mg/kgAcute dermal toxicity Skin irritation (OECD 439, human) Skin irritation

Eye irritation No eye irritation (QSAR)

Sensitisation Causes sensitisation. (OECD 429, Mouse)

#### 12. ECOLOGICAL INFORMATION

**Elimination information (persistence and degradability)** 

Biodegradability : Not readily biodegradable. (11 %, 28 d, OECD 301 C)

**Ecotoxicity effects** 

Toxicity to fish LC50(96 h, Lepomis macrochirus (Bluegill sunfish)) = 1.3 mg/l

(OECD Test Guideline 203)

Toxicity to daphnia and other

aquatic invertebrates

EC50(48 h, Daphnia magna (Water flea)) = 1.38 mg/l (OECD Test

Guideline 202)

Toxicity to algae EC50(72 h, Desmodesmus subspicatus (green algae)) = 2.6 mg/l

(OECD Test Guideline 201)

Toxicity to bacteria NOEC(42 h, ) = > 100 mg/l (OECD 301 F)

#### 13. DISPOSAL CONSIDERATIONS

Product Disposal together with normal waste is not allowed. Special disposal

required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site

for recycling or disposal.

Version

Revision Date : 04.03.2015



Product TIMBERSILK

Print Date 28.04.2015 Page 6 (7)

#### 14. TRANSPORT INFORMATION

**IATA** 

UN number : 3082

 $\label{eq:Description} Description of the goods \qquad \qquad : \qquad Environmentally \ hazardous \ substance, \ liquid, \ n.o.s.$ 

(Octahydro Tetramethyl Naphthalenyl Ethanone)

Labels : 9 Packing group : III

IMDG GLOBAL

UN number : 3082

Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S

(Octahydro Tetramethyl Naphthalenyl Ethanone)

Labels : 9
Packing group : III
Marine pollutant : yes

#### 15. REGULATORY INFORMATION

Labelling according to EC Directives 67/548/EEC

Symbol(s) : Xi Irritant

N Dangerous for the environment

R-phrase(s) : R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

S-phrase(s) : S24 Avoid contact with skin.

S37 Wear suitable gloves.

S61 Avoid release to the environment. Refer to special

instructions/ Safety data sheets.

**HMIS Classification** : Health hazard: 2

Flammability: 1

Physical and chemical hazards: 0

#### 16. OTHER INFORMATION

#### **Further information**

The information in this safety data sheet is based on the properties of the material known to IFF at the time the data sheet was issued. The safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances under which it is packaged, stored or applied in the workplace. For such a

Version : 4

Revision Date : 04.03.2015



Product TIMBERSILK

Print Date 28.04.2015 Page 7 (7)

safety assessment International Flavors & Fragrances holds no responsibility. This document is not intended for quality assurance purposes.

Version : 4

Revision Date : 04.03.2015